

T 2 SERIES LIGHT TUBE

| | |
|---------------------|---|
| Product name | Prolucent T2 |
| Description | Linear dual color , low voltage light tube |
| Benefits | Cost efficient , easy to install, versatile Color changing, influence on behavior of poultry, reduction of ground eggs, stress and pecking reduction |
| Material | PMMA with PVC ends |
| IP rating | IP69K |
| Connectors | Interconnectable system : 2/ 3 pin connector (T1 series = 2 pin , T2 series = 3 pin) |
| Dimensions | See drawing. A: 1830 mm (720,5") , B: 2540 mm (1000") |
| Voltage | 24V and 48V version available |
| Power | 2 x 5,5W |
| Working temperature | 45°C , 113°F |
| Protection | internal resettable fuse Internal backwire of 1,5mm ² (16 AWG) Low resistance connectors |
| Lens | Frosted |
| Leds | 72 leds driven at low current |
| Dimmable | 0-100% |
| Lumen output | See product list |
| Color output | Different led colours available |
| Accessories | Mounting clamps , cabling, dimmers |



T2 series Dual color low voltage light tube
BiColour tube 725" - Warm White 3000K - Blue - 2 x 5.5W
BiColour tube 725" - Special White - Red - 2 x 5.5W

24V Version
on request
on request

48V Version
PLT2-48-3000-0470-L1-W5,5-V2
PLT2-48-SP1-0625-L1-W5,5-V2

